

MV-CA016-10GM/GC

1.6 MP 1/2.9" CMOS GigE Area Scan Camera



GEN<I>CAM

GiGE
VISION


Introduction

MV-CA016-10GM/GC camera adopts Sony® IMX 273 sensor and provides high quality image. The GigE interface provides high-speed and real-time transmission of uncompressed data with the maximum frame rate reaching 78.2 fps at full resolution.

Key Feature

- Adopts GigE interface and max. transmission distance of 100 meters without relay.
- Supports auto and manual adjustment for exposure control, LUT, Gamma correction, etc.
- Up to 128 MB local memory for burst transmission and retransmission.
- Supports hardware trigger, software trigger, etc.
- Compatible with GigE Vision Protocol V2.0, GenICam Standard, and third-party software based on these protocol and standard.

Dimension



Unit: mm


Available Model

- Mono camera: MV-CA016-10GM
- Color camera: MV-CA016-10GC


Applicable Industry

Electronic semiconductor, factory automation, and quality inspection, etc.

Sensor Quantum Efficiency



MV-CA016-10GM



MV-CA016-10GC



en.hikrobotics.com

Specification

Model	MV-CA016-10GM	MV-CA016-10GC
Camera		
Sensor type	CMOS, global shutter	
Sensor model	Sony® IMX273	
Pixel size	3.45 μ m \times 3.45 μ m	
Sensor size	1/2.9"	
Resolution	1440 \times 1080	
Max. frame rate	78.2 fps @1440 \times 1080	
Dynamic range	71.4 dB	
SNR	41 dB	
Gain	0 dB to 20 dB	
Exposure time	1 μ s to 10 sec	
Exposure mode	Off/ Once /Continuous exposure mode	
Mono/color	Mono	Color
Pixel format	Mono 8/10/10p/12/12p	Mono8/10/12, Bayer RG 8/10/10p/12/12p YUV 422 Packed, YUV422_YUYV_Packed, RGB8
Binning	Supports 1 \times 1, 2 \times 2	
Decimation	Supports 1 \times 1, 2 \times 2	
Reverse image	Supports horizontal and vertical reverse image output	
Image buffer	128 MB	
Electrical feature		
Data interface	Gigabit Ethernet, compatible with Fast Ethernet	
Digital I/O	6-pin Hirose connector provides power and I/O, including opto-isolated input \times 1 (Line 0), opto-isolated output \times 1 (Line 1), bi-directional non-isolated I/O \times 1 (Line 2).	
Power supply	9 VDC to 24 VDC, supports PoE	
Power consumption	Typ. 3 W@12 VDC	
Mechanical		
Lens mount	C-Mount	
Dimension	29 mm \times 29 mm \times 42 mm (1.1" \times 1.1" \times 1.7")	
Weight	Approx. 68 g (0.15 lb)	
Ingress protection	IP 30 (under proper lens installation and wiring)	
Temperature	Working temperature: 0 °C to 50 °C (32 °F to 122 °F) Storage temperature: -30 °C to 70 °C (-22 °F to 158 °F)	
Humidity	20% to 80% RH, non-condensing	
General		
Client software	MVS or third-party software meeting with GigE Vision Protocol	
Operating system	32/64-bit Windows XP/7/10, 32/64-bit Linux and 64-bit MacOS	
Compatibility	GigE Vision V2.0, GenICam	
Certification	CE, FCC, RoHS	

HIKROBOT

Hangzhou Hikrobot Technology Co.,Ltd.

No.399 Danfeng Road, Binjiang District, Hangzhou 310051, China.

en.hikrobotics.com

Copyright Hikrobot

Hangzhou Hikrobot Technology Co., Ltd. All Rights Reserved. Hangzhou Hikrobot Technology does not tolerate any infringement. Any organization or individual may not imitate or reproduce in whole or in part of the content. The data herein is based on Hikrobot's internal evaluation. Actual data may vary depending on specific configuration and operating condition. The information herein is subject to change without notice. All the content has been checked conscientiously. Nevertheless, Hikrobot shall not be liable to damages resulting from errors, inconsistencies or omissions.